



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a**

Specifications	LUZON 3.75	LUZON 3.13	LUZON 2.50	LUZON 1.88	LUZON 1.56	LUZON 1.25	LUZON 0.94
CODE	BA280	BA270	BA260	BA250	BA240	BA230	BA220
Length [mm]	3830	3210	2580	1960	1645	1330	1020
Usable storage capacity [dm <sup>3</sup> ]	729	609	486	366	303	243	183
Shelf area [m <sup>2</sup> ]	2,9	2,4	1,9	1,4	1,2	1	0,7
Side panel thickness [mm]	40	40	40	40	40	40	40
Depth [mm]	1180	1180	1180	1180	1180	1180	1180
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Refrigerant/Cooling factor	R404A / R507R404A / R507R404A / R507R404A / R507R134a				R134a		R134a
Evaporating temperature [°C]	-15	-15	-15	-15	-15	-15	-15
Cooling power demand [W/mb]	350	350	350	350	350	350	350
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	51	43,2	28,8	22,4	22,4	17	14,4
Rated power [W]	940	677	599	435	365	290	287
Cooling power [W]	1287	1050	719	511	464	348	348
Electricity consumption [kWh/24h]	13,2	9,5	8,4	6,1	5,1	4,1	4

## Standard equipment

internal cooling aggregate

device prepared for multiplexing

static cooling

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of white coated steel

storage chamber made of white coated steel

storage chamber back doors - hinged

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

LED lamp (color of choice: white, confectionery or meaty “deep pink”)

bumper - different colors available (IGLOO pattern book)

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

## Options

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

wooden sides + glass sides - selectable colour (IGLOO colour chart)

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of stainless steel

storage chamber made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

exposition area - stepped - 2 steps

exposition area - stepped - 3 steps

powder painted evaporator

night blinds made of plexi glass

worktop - granite grey (thickness : 20 mm)

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

additional exposition glass shelf

set of wheels (castors)

fans enforcing air circulation

additional LED light in top lamp profile

automatic defrost

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

automatic condenser vaporization

analog thermometer

electronic temperature recorder + software

recorder cable

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

