



Temperature range:

Refrigerating unit:

Refrigerant/Cooling factor:

Specifications	JUSTYNA 2.0	JUSTYNA 2.5
KOD	JS100	JS101
Length [mm]	1990	2610
Length with the sides [mm]	1990	2610
Capacity [dm ³]	290	362
Working capacity of the chamber [dm ³]	290	362
The area of shelves [m ²]	1,45	1,81
Exhibition area [m ²]	1,45	1,81
Depth [mm]	1030	1030
Height [mm]	960+/10	960+/10
Unit weight [kg]	210	260
Refrigerant	R404a R507 R448 R449	R404a R507 R448 R449
Rated voltage [V]	230/50Hz	230/50Hz
Rated power of lighting [W]	44,8	44,8
Rated power [W]	1817	1827
Cooling power [W]	1488	1488
Rated power of electric heaters [W]	2256	3038
Rated power of the evaporator heater [W]	2210	3000

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

external housing made of coated steel – different colors available (igloo pattern book)

base made of white coated steel

ecological polyurethane foam insulation

bumper – different colors available (IGLOO pattern book)

exposition area made of white coated steel

lamp with LED light (white color)

ABS side panels – different colors available (IGLOO pattern book)

device leveling legs

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

Options

external top housing color - different colors available (IGLOO pattern book)

base color - different colors available (IGLOO pattern book)

external top housing made of stainless steel

base made of stainless steel

exposition area made of stainless steel

exposition area made of acid resistant stainless steel

horizontal night roller blinds

electronic temperature recorder + software

temperature recorder wire (RS232 - USB)

movable partition (low ,glass on stands , placed in exposition area)

top with shelf

top with shelf and illumination

glass movable covers

device with temperature range from +1 °C to +10 °C (cooling version)

insulated ABS side panels - different colors available (IGLOO pattern book) - thickness : 40 mm

