



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

| Name | PARIS 0.94 | PARIS 1.25 | PARIS 1.56 | PARIS 1.88 | PARIS 2.50 | PARIS 3.13 | PARIS 3.75 | PARIS NZ90 |
|--|---|------------|------------|------------|------------|------------|------------|------------|
| Code | PRS120 | PRS130 | PRS140 | PRS150 | PRS160 | PRS170 | PRS180 | PRS195 |
| Length [mm] | 938 | 1250 | 1563 | 1875 | 2500 | 3125 | 3750 | - |
| Height [mm] | 1050 ± 10 | 1050 ± 10 | 1050 ± 10 | 1050 ± 10 | 1050 ± 10 | 1050 ± 10 | 1050 ± 10 | 1050 ± 10 |
| Depth [mm] | 920 | 920 | 920 | 920 | 920 | 920 | 920 | 920 |
| Capacity [dm ³] | 56,3 | 75 | 94 | 113 | 150 | 188 | 225 | - |
| Display area [m ²] | 0,56 | 0,8 | 0,9 | 1,1 | 1,5 | 1,9 | 2,3 | 0,8 |
| Total Display Area (TDA) [m ²] | 0,60 | 0,80 | 1,00 | 1,21 | 1,61 | 2,01 | 2,41 | 0,80 |
| Temp. range [°C] | (+1 ± +10°C) (+1 ± +10°C) (+1 ± +10°C) (+1 ± +10°C) (+1 ± +10°C) (+1 ± +10°C) (+1 ± +10°C) (+1 ± +10°C) | | | | | | | |
| Temp. class | 3H1 3H1 3H1 3H1 3H1 3H1 3H1 3H1 | | | | | | | |
| Climate class | 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) 3 (25°C ; 60% RH) | | | | | | | |
| Energy efficiency class | E E E E E E E - | | | | | | | |
| Refrigerant | R290 R290 R290 R290 R290 R290 R290 R290 | | | | | | | |
| Rated voltage [V] | 230/50Hz 230/50Hz 230/50Hz 230/50Hz 230/50Hz 230/50Hz 230/50Hz 230/50Hz | | | | | | | |
| Rated power [W] | 237 412,5 532 551 641 699,5 748 413 | | | | | | | |



The presented class applies to selected device modules. The classes for the individual modules may differ. The indication of the energy class for the selected device configuration is given on the attached label.

Standard equipment

internal unit

dynamic cooling (ventilated)

automatic off-cycle defrosting

automatic evaporation of condensate

electronic temperature controller with digital display

IGLOO / CAREL

INOX display area

MELAMINE storage area

IGLOO pattern book

PES coated storage area

model "Z" - RAL9010

LED lighting

IGLOO pattern book

AC fans

MELAMINE external housing

FRONT - IGLOO pattern book

powder coated external housing

REAR - IGLOO pattern book

| | |
|--|---|
| INOX worktop | |
| straight front glass | openable |
| profile AL | IGLOO pattern book |
| MELAMINE sides | IGLOO pattern book |
| sliding back doors | model "Z" - 0.94 - hinged, NZ90 - no door |
| INOX / MELAMINE base plinth | FRONT / REAR |
| ecological polyurethane foam insulation | |
| audible alarm on the condenser pollution | |

Options

| |
|--|
| powder coated external housing - REAR - custom powder - (after consultation with the IGLOO Sales Department) |
| INOX external housing - REAR |
| INOX AISI304 external housing - REAR |
| front panel made of MELAMINE - custom decors - (after consultation with the IGLOO Sales Department) |
| sides made of MELAMINE - custom decors - (after consultation with the IGLOO Sales Department) |
| front panel made of VENEER or TREND - different decors available (IGLOO pattern book) |
| sides made of VENEER or TREND - different decors available (IGLOO pattern book) |
| powder-coated display surface - choice of colour (IGLOO chart) |
| INOX AISI304 display area |
| INOX AISI304 worktop |
| granite worktop balmoral |
| granite worktop black |
| INOX storage area |
| INOX AISI304 storage area |
| sliding doors system made of MELAMINE - REAR - selectable colour (IGLOO pattern book) |
| humidity control system |
| night blinds made of plexi glass |
| powder painted evaporator |
| automatic defrost |
| set of wheels (castors) - (model 0.94 / 1.25) |
| set of wheels (castors) - (model 1.56 / 1.88 / 2.50 / 3.13 / 3.75) |
| LED lighting of base plinth |
| display space thermometer |
| runner for small movable table |
| small movable table for scale or cash register (400x500mm) |

