



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290 / R449**

Name	BASIA NEO 0.94	BASIA NEO 1.25	BASIA NEO 1.56	BASIA NEO 1.88	BASIA NEO 2.50	BASIA NEO 3.13	BASIA NEO 3.75	BASIA NEO NW90	BASIA NEO NZ90
Code	BN120	BN130	BN140	BN150	BN160	BN170	BN180	BN190	BN195W
Length [mm]	938	1250	1563	1875	2500	3125	3750	-	-
Height [mm]	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10
Depth [mm]	1155	1155	1155	1155	1155	1155	1155	1155	1155
Capacity [dm <sup>3</sup> ]	115	155	193	233	310	388	465	-	-
Display area [m <sup>2</sup> ]	0,9	1,2	1,2	1,8	2,4	3,0	3,6	-	-
Total Display Area (TDA) [m <sup>2</sup> ]	-	-	-	-	-	-	-	-	-
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	3H1	3H1	3H1	3H1	3H1	3H1	3H1	3H1	3H1
Climate class	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )
Energy efficiency class	-	-	-	-	-	-	-	-	-
Refrigerant	R290	R290	R290	R290	R290	R449	R449	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	354	382	389	467	533	1179	1194	382	-



The presented class applies to selected device modules. The classes for the individual modules may differ. The indication of the energy class for the selected device configuration is given on the attached label.

## Standard equipment

internal cooling aggregate

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

static cooling

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

storage chamber back doors - hinged (not applicable to corners)

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)  
curved front glass openable  
LED lamp (color of choice: white, confectionery or meaty "deep pink")  
bumper - different colors available (IGLOO pattern book)  
insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)  
automatic defrost  
condenser outlet to container  
analog thermometer  
electronic temperature controller with digital display (IGLOO)  
condenser impurity or fan operation failure alarm

## Options

device prepared for multiplexing  
device without side panels prepared for multiplexing (MOD/A)  
housing with base panel from staff side made of stainless steel  
front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)  
front panel color - different colors available (IGLOO pattern book)  
custom front panel color (after consultation with the IGLOO Sales Department)  
base panel made of stainless steel  
display space with coloured sheet - selectable colour (IGLOO colour chart)  
storage chamber made of stainless steel  
exposition area made of acid resistant stainless steel  
storage chamber made of acid - resistant stainless steel  
exposition area - stepped - 2 steps  
exposition area - stepped - 3 steps  
powder painted evaporator  
night blinds made of plexi glass  
worktop - granite grey (thickness - 20 mm)  
worktop - granite Balmoral (thickness : 20 mm)  
worktop - granite black (thickness : 20 mm)  
additional exposition glass shelf  
delivery overlay for the stainless steel panel front window  
set of wheels (castors)  
fans enforcing air circulation  
additional LED light in top lamp profile  
automatic defrost  
the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)  
automatic condenser vaporization  
electronic temperature recorder + software

