


 Temperature range: **+5°C/+15°C**

 Refrigerating unit: **Internal**

 Refrigerant/Cooling factor: **R134a**

Specifications	GASTROLINE CUBE 0.6W	GASTROLINE CUBE 0.9W	GASTROLINE CUBE 1.3W
CODE	GC103	GC102	GC101
Length [mm]	610	910	1310
Length with the sides [mm]	610	910	1310
Capacity [dm ³]	0,87	1,3	1.9
Working capacity of the chamber [dm ³]	320	480	690
The area of shelves [m ²]	0,84	1,3	1,9
Depth [mm]	835	835	835
Height [mm]	1270+/-10	1270+/-10	1270+/-10
Unit weight [kg]	90	140	180
Shelves dimensions [mm]	570x425 1szt, 570x515 1szt, 290x525 2szt	870x425 1szt, 870x515 1szt, 440x525 2szt	1280x425 1szt, 1280x515 1szt, 640x525 2szt
Refrigerant/Cooling factor	R134a	R134a	R134a
Evaporating temperature [°C]	-10	-10	-10
Cooling power demand [W/mb]	800	800	800
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	21,6	25,5	51
Rated power [W]	309	542	715
Cooling power [W]	461	727	1025
Rated power of the evaporator heater [W]	160	160	200
Electricity consumption [kWh/24h]	4,6	7,9	10,4

Standard equipment

internal cooling aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

external housing made of black coated steel

side panels made of black coated steel

wooden melamine front panel with stainless steel or mirror strip - different colors available (IGLOO pattern book)

glass side panels or combined glass divider for multiplexable devices

straight front glass

ecological polyurethane foam insulation

internal frame painted silver or gold (IGLOO pattern book)

2 pcs of glass exposition shelves with height and angle adjustment placed on the frame

wooden bottom internal melamine shelf - different colors available (IGLOO pattern book)

back sliding doors with combined glass (GASTROLINE CUBE 0.6 - hinged doors with choice of door opening direction)

upper interior lighting + additional illumination of each shelf - LED lights (confectionery color)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display

condenser impurity or fan operation failure alarm

Options

device without side panels prepared for multiplexing (MOD/A)

side panels made of colored coated steel - different colors available (IGLOO pattern book)

wooden front (veneer panel) or TREND - selectable colour (IGLOO colour chart)

front panel with color-coated sheet - selectable color (IGLOO color guide)

internal frame made of stainless steel for 0.6 model

internal frame made of stainless steel for 0.9 model

internal frame made of stainless steel for 1.3 model

bottom shelf made of stainless steel

humidity control system

electronic temperature recorder + software

recorder cable

small tray (400mm x 340mm)

small tray (400mm x 420mm)

medium tray (400mm x 510mm)

bottom tray (400mm x 520mm)

set of wheels (castors)

