



Temperature range: **+5°C/+15°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a**

Specifications	KAMELEO 0.6 W	KAMELEO 0.9 W	KAMELEO 1.3 W
CODE	JA103K	JA102K	JA101K
Length [mm]	705	1005	1405
Length with the sides [mm]	705	1005	1405
Capacity [dm <sup>3</sup> ]	334	496	715
Working capacity of the chamber [dm <sup>3</sup> ]	334	496	715
The area of shelves [m <sup>2</sup> ]	1,2	1,8	2,6
Side panel thickness [mm]	38	38	38
Depth [mm]	960 +/-5	960 +/-5	960 +/-5
Height [mm]	1360 +/-10	1360 +/-10	1360 +/-10
Unit weight [kg]	120	170	220
Shelves dimensions [mm]	570x425 1szt, 570x515 1szt, 570x595 1szt, 290x525 2szt	870x425 1szt, 870x515 1szt, 870x595 1szt, 440x525 2szt	1280x425 1szt, 1280x515 1szt, 1280x595 1szt, 640x525 2szt
Refrigerant	R134a	R134a	R134a
Evaporating temperature [°C]	-10	-10	-10
Cooling power demand [W/mb]	800	800	800
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	28,8	34	68
Rated power [W]	316	551	732
Cooling power [W]	461	727	1025
Rated power of the evaporator heater [W]	160	160	200
Electricity consumption [kWh/24h]	4,7	8	10,6

## Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

front panel and plinth, wooden base - colour selectable (IGLOO colour chart)

small and thin wooden side panels - different colors available (IGLOO pattern book)

glass side panels or combined glass divider for multiplexable devices

curved front glass openable

ecological polyurethane foam insulation

---

internal frame painted silver or gold (IGLOO pattern book)

---

glass exposition shelves with height and angle adjustment placed on the frame

---

bottom shelf made of stainless steel

---

back sliding doors with combined glass (KAMELEO 0.6 - hinged doors with choice of door opening direction)

---

upper interior lighting + additional illumination of each shelf - LED lights (confectionery color)

---

automatic defrost

---

automatic condenser vaporization

---

electronic temperature controller with digital display

---

condenser impurity or fan operation failure alarm

---

## Options

the device without the wooden sides adapted for serial connection (mod/A)

---

small and thin wooden side panels - different colors available (IGLOO pattern book)

---

additional base plinth - different colors available (IGLOO pattern book)

---

additional front panel - different colors available (IGLOO pattern book)

---

additional side panels - different colors available (IGLOO pattern book)

---

additional thin side panels - different colors available (IGLOO pattern book)

---

internal frame made of stainless steel for 0.6 model

---

internal frame made of stainless steel for 0.9 model

---

internal frame made of stainless steel for 1.3 model

---

humidity control system

---

electronic temperature recorder + software

---

temperature recorder wire

---

small tray (400mm x 420mm)

---

medium tray (400mm x 510mm)

---

big tray (400mm x 590mm)

---

bottom tray (400mm x 520mm)

---

# KAMELEO (W)

