



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Specifications	LUNA 1440.90	LUNA 1440.188	LUNA 1440.313
Length [mm]	900	1880	3130
Height [mm]	1440±10	1440±10	1440±10
Depth [mm]	660	660	660
Refrigerant	R290	R290	R290
Capacity [dm ³]	171	260	361
Cooling area of shelves [m ²]	0,77	1,16	1,62
Rated power [W]	886	1408	1508
Prąd znamionowy [A]	5,9	9,6	10,0
Prąd znamionowy wyparka [A]	2,0	3,5	3,5
Napięcie znamionowe [V/hz]	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	40	60	88
Moc znamionowa grzałek wyparki [W]	460	800	800
Electricity consumption [kWh/24h]	6,9	10,1	11,5

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

external housing, interior and frame made of powder painted steel - different colors available (IGLOO pattern book)

exposition shelves on frame made of powder painted steel - different colors available (IGLOO pattern book)

price stripes - different colors available (IGLOO pattern book)

ecological polyurethane foam insulation

side glass with silk-screen printing

upper interior lighting + additional illumination of each shelf - LED lights (confectionery color)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

external housing color - different colors available (IGLOO pattern book)

external housing made of stainless steel

interior colour - possibility of choosing the color (IGLOO pattern book)

interior and frame made of stainless steel sheet

exposition shelves on frame made of stainless steel

electronic temperature recorder + software

recorder cable

