



Temperature range:

Refrigerating unit: **External**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Specifications	LUZON DEEP 0.94-mod/C	LUZON DEEP 1.25-mod/C	LUZON DEEP 1.56-mod/C	LUZON DEEP 1.88-mod/C	LUZON DEEP 2.50-mod/C	LUZON DEEP 3.13-mod/C	LUZON DEEP 3.75-mod/C
CODE	BA220WG-c	BA230WG-c	BA240WG-c	BA250WG-c	BA260WG-c	BA270WG-c	BA280WG-c
Length [mm]	938	1250	1563	1875	2500	3125	3750
Usable storage capacity [dm ³]	140	186	232	280	372	466	558
Shelf area [m ²]	0,9	1,1	1,4	1,7	2,3	2,8	3,4
Side panel thickness [mm]	40	40	40	40	40	40	40
Depth [mm]	1180	1180	1180	1180	1180	1180	1180
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Refrigerant	R404a R507 R448 R449	R404a R507 R448 R449	R404a R507 R448 R449	R404a R507 R448 R449	R404a R507 R448 R449	R404a R507 R448 R449	R404a R507 R448 R449
Evaporating temperature [°C]	-10	-10	-10	-10	-10	-10	-10
Cooling power demand [W/mb]	400	400	400	400	400	400	400
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	14	17	22	34	44	51	61
Rated power [W]	40	46	49	86	92	139	139
Electricity consumption [kWh/24h]	0,6	0,7	0,7	1,3	1,4	2,1	2,1

Standard equipment

powered only by external aggregate

device without side panels prepared for multiplexing (MOD/A)

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of white coated steel

storage chamber made of white coated steel

rear storage compartment door - hinged (not applicable to corners)

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

LED lamp (color of choice: white, confectionery or meaty "deep pink")

bumper - different colors available (IGLOO pattern book)

automatic defrost

electronic temperature controller with digital display (IGLOO)

Options

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

wooden sides + glass sides - selectable colour (IGLOO colour chart)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of stainless steel

storage chamber made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

exposition stepped overlay made of white coated steel (1 step)

exposition stepped overlay made of stainless steel (1 step)

exposition stepped overlay made of acid resistant stainless steel (1 step)

exposition stepped overlay made of white coated steel (2 steps)

exposition stepped overlay made of stainless steel (2 step)

exposition stepped overlay made of acid resistant stainless steel (2 step)

powder painted evaporator

night blinds made of plexi glass

worktop - granite grey (thickness : 20 mm)

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

additional exposition glass shelf

additional LED light in top lamp profile

automatic defrost

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

analog thermometer

electronic temperature recorder + software

recorder cable

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart)
(excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

