



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Specifications	LUZON DEEP 0.94	LUZON DEEP 1.25	LUZON DEEP 1.56	LUZON DEEP 1.88	LUZON DEEP 2.50	LUZON DEEP 3.13	LUZON DEEP 3.75
CODE	BA220WG	BA230WG	BA240WG	BA250WG	BA260WG	BA270WG	BA280WG
Length [mm]	1020	1330	1645	1960	2580	3210	3830
Usable storage capacity [dm <sup>3</sup> ]	140	186	232	280	372	466	558
Shelf area [m <sup>2</sup> ]	0,9	1,1	1,4	1,7	2,3	2,8	3,4
Side panel thickness [mm]	40	40	40	40	40	40	40
Depth [mm]	1180	1180	1180	1180	1180	1180	1180
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Refrigerant	R404a R507 R448 R449	R404a R507 R448 R449	R404a R507 R448 R449	R134a R290	R134a R290	R134a R290	R134a R290
Evaporating temperature [°C]	-10	-10	-10	-10	-10	-10	-10
Cooling power demand [W/mb]	400	400	400	400	400	400	400
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	14	17	22	34	44	51	61
Rated power [W]	40	46	49	86	92	139	139
Electricity consumption [kWh/24h]	0,6	0,7	0,7	1,3	1,4	2,1	2,1

## Standard equipment

internal cooling aggregate

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of white coated steel

storage chamber made of white coated steel

---

rear storage compartment door - hinged (not applicable to corners)

---

worktop - stainless steel

---

anodised aluminum profiles color gold or silver (IGLOO pattern book)

---

straight front glass pane (which can slightly be opened)

---

LED lamp (color of choice: white, confectionery or meaty "deep pink")

---

bumper - different colors available (IGLOO pattern book)

---

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

---

automatic defrost

---

condenser outlet to container

---

electronic temperature controller with digital display (IGLOO)

---

condenser impurity or fan operation failure alarm

---

## Options

device prepared for multiplexing

---

wooden sides + glass sides - selectable colour (IGLOO colour chart)

---

device without side panels prepared for multiplexing (MOD/A)

---

housing with base panel from staff side made of stainless steel

---

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

---

front panel color - different colors available (IGLOO pattern book)

---

custom front panel color (after consultation with the IGLOO Sales Department)

---

base panel made of stainless steel

---

exposition area made of stainless steel

---

storage chamber made of stainless steel

---

exposition area made of acid resistant stainless steel

---

storage chamber made of acid - resistant stainless steel

---

exposition stepped overlay made of white coated steel (1 step)

---

exposition stepped overlay made of stainless steel (1 step)

---

exposition stepped overlay made of acid resistant stainless steel (1 step)

---

exposition stepped overlay made of white coated steel (2 steps)

---

exposition stepped overlay made of stainless steel (2 step)

---

exposition stepped overlay made of acid resistant stainless steel (2 step)

---

powder painted evaporator

---

night blinds made of plexi glass

---

worktop - granite grey (thickness : 20 mm)

---

worktop - granite Balmoral (thickness : 20 mm)

---

worktop - granite black (thickness : 20 mm)

---

additional exposition glass shelf

---

set of wheels (castors)

---

additional LED light in top lamp profile

---

automatic defrost

---

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

---

automatic condenser vaporization

---

analog thermometer

---

electronic temperature recorder + software

recorder cable

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart)  
(excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

