



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a**

Specifications	MAX
CODE	MX100
Length [mm]	540
Usable storage capacity [dm ³]	118
Shelf area [m ²]	1,2
Side panel thickness [mm]	40
Depth [mm]	660
Height [mm]	1260+/-15
Refrigerant/Cooling factor	R134a
Evaporating temperature [°C]	-10
Cooling power demand [W/mb]	435
Rated voltage [V]	230/50Hz
Rated power of lighting [W]	7
Rated power [W]	435
Cooling power [W]	524
Electricity consumption [kWh/24h]	6,1

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

insulated plastic sides with insulated glass - selectable colour (IGLOO colour chart)

ecological polyurethane foam insulation

base panels, upper and lower front panel with coloured sheet - selectable colour (IGLOO colour chart)

rack interior with coloured sheet - selectable colour (IGLOO colour chart)

interior lighting - fluorescent LED

glass exposition shelves

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

custom colors of top front panel

top full panel made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base made of stainless steel

interior colour - possibility of choosing the color (IGLOO pattern book)

interior made of stainless steel

interior made of acid resistant steel

electronic temperature recorder + software

recorder cable

