



Temperature range: **-12°C/-18°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404A / R507**

Specifications	OLA 1400.2 M
CODE	OL100.2/M
Length [mm]	1675
Capacity [dm ³]	1400
Working capacity of the chamber [dm ³]	1400
The area of shelves [m ²]	4,4
Polyurethane foam insulation thickness [mm]	60
Depth [mm]	800
Height [mm]	2000 +/10
Shelves dimensions [mm]	510x710
Maximum load [kg/m]	30
Refrigerant/Cooling factor	R404A / R507
Evaporating temperature [°C]	-30
Rated voltage [V]	230/50Hz
Rated power of lighting [W]	39,4
Rated power [W]	1207
Cooling power [W]	1043
Rated power of electric heaters [W]	245
Rated power of the evaporator heater [W]	790
Electricity consumption [kWh/24h]	16,1

Standard equipment

internal freezing aggregate placed on the bottom

dynamic cooling (ventilated)

external housing made of coated steel – different colors available (Igloo pattern book)

interior made of white coated steel

drzwi rozwierne z podgrzewaną szybą zespoloną

ecological polyurethane foam insulation

hinged doors self – closer

heated door frame

10 pcs of plastified reticulated shelves, with position adjustment

price stripes – different colors available (IGLOO pattern book)

top panel illuminated with LED light – different plexiglass colors available (IGLOO pattern book)

automatic defrost

automatic condenser vaporization

oświetlenie pionowe wnętrza - świetlówki LED

fan stopping switch

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

external housing color - different colors available (IGLOO pattern book)

external housing made of stainless steel

interior made of stainless steel

przegroda stała z blachy nierdzewnej (nie hermetyczna)

door lock with key

plastified strengthened shelves

chrome reticulated shelves

chrome strengthened reticulated shelves

additional plastified reticulated shelf + handle set

additional plastified reticulated strengthened shelf + handle set

additional chrome reticulated shelf + handle set

additional chrome reticulated strengthened shelf + handle set

internal top and side illumination - LED lights

electronic temperature recorder + software

temperature recorder wire (RS232 - USB)

SMS alarm module + temperature recorder with emergency power supply

USB - MGSM TTL wire for SMS module programming

