



Temperature range: **+2°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a**

Specifications	PETRO 0.6	PETRO 0.9
CODE	PR100	PR101
Length [mm]	600	900
Capacity [dm3]	240	370
Cooling area of shelves [m2]	0,8	1,2
Side panel thickness [mm]	18	18
Depth [mm]	755	755
Height [mm]	1400+/-10	1400+/-10
Refrigerant/Cooling factor	R134a	R134a
Evaporating temperature [°C]	-10	-10
Rated voltage [V]	230/50Hz	230/50Hz
Rated power of lighting [W]	34	56
Rated power [W]	304	573
Cooling power [W]	460	727
Electricity consumption [kWh/24h]	4,4	9,9

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

external housing, interior and frame made of powder painted steel - different colors available (IGLOO pattern book)

glass exposition shelves on frame

price stripes - different colors available (IGLOO pattern book)

ecological polyurethane foam insulation

bent front glass unit with silk-screen printing

side glass with silk-screen printing

back sliding doors with combined glass (PETRO 0.6 - hinged doors with choice of door opening direction)

upper interior lighting + additional illumination of each shelf - LED lights (confectionery color)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display at the base of the device, from the customer's side

condenser impurity or fan operation failure alarm

Options

external housing color - different colors available (IGLOO pattern book)

external housing made of stainless steel

front panel made of melamine board - different colors available (IGLOO pattern book)

wooden front panel made of veneer or TREND - different colors available (IGLOO pattern book)

interior colour - possibility of choosing the color (IGLOO pattern book)

interior and frame made of stainless steel sheet

electronic temperature recorder + software

temperature recorder wire

PETRO

