



Temperature range: **3M1 (-1/+5°C) / 3M2 (-1/+7°C) / 3H1 (+1/+10°C)**

Refrigerating unit: **External**

Refrigerant/Cooling factor:

Specifications	Proxima 1.25	Proxima 1.88	Proxima 2.50	Proxima 3.75
CODE	PRX130	PRX150	PRX160	PRX180
Length [mm]	1250	1875	2500	3750
Depth [mm]	1153	1153	1153	1153
Height [mm]	1103+/-10	1103+/-10	1103+/-10	1103+/-10
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz

Standard equipment

powered only by external aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

external housing made of white coated steel (from the staff side)

front panel with color-coated sheet - selectable color (IGLOO color guide)

stainless steel base with adjustable span

ecological polyurethane foam insulation

display space with coloured sheet - selectable colour (IGLOO colour chart)

worktop - stainless steel

front glass - telescopic lifting system

silver aluminum profiles

display space thermometer

automatic defrost (electric heaters)

electronic temperature controller with digital display (IGLOO)

modern LED lighting (lighting colour options: white confectionery, pink)

Options

side glass with silk - screen printing

external housing made of stainless steel (from staff side)

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

exposition area made of stainless steel

exposition area made of acid resistant stainless steel

1-degree display extension with coloured sheet

exposition stepped overlay made of stainless steel (1 step)

exposition stepped overlay made of acid resistant stainless steel (1 step)

2-degree display extension with coloured sheet

exposition stepped overlay made of stainless steel (2 step)

exposition stepped overlay made of acid resistant stainless steel (2 step)

powder painted evaporator

night blinds made of plexi glass

worktop - acid-resistant stainless steel

front buffer with stainless steel profile

front shelf for the customer with silver or gold aluminium profiles

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart)

movable partition (low, glass on stands, placed in exposition area)

fixed partition (high, glass in exposition area stainless steel in storage chamber)

runner for small movable table

small movable table for scale or cash register (400x500mm)

additional innovative LED lighting in the upper lamp profile (selectable light colour)

socket with fuse

electronic temperature regulator with the registration system (Igloo)

recorder cable

no thermostat - 2 x temperature sensor NTC [10kΩ]

electronic expansion valve with controlling regulator (Carel / Danfoss)

cooling system adopted to factor R744 (CO2) (only with electronic expansion valve)

