



Temperature range: **+1°C/+10°C**

Refrigerating unit: **External**

Refrigerant/Cooling factor: **R404A / R507**

Specifications	SANTIAGO 1.1 WG-mod/C	SANTIAGO 1.4 WG-mod/C	SANTIAGO 1.7 WG-mod/C	SANTIAGO 2.1 WG-mod/C	SANTIAGO 2.5 WG-mod/C	SANTIAGO 3.75 WG-mod/C
CODE	SA100WG-c	SA101WG-c	SA102WG-c	SA103WG-c	SA104WG-c	SA180WG-c
Length [mm]	960	1290	1590	1920	2460	3750
Capacity [dm ³]	143	192	237	286	366	558
Cooling area of shelves [m ²]	0,86	1,16	1,43	1,73	2,21	3,38
Side panel thickness [mm]	40	40	40	40	40	40
Depth [mm]	1190	1190	1190	1190	1190	1190
Height [mm]	1225+/-10	1225+/-10	1225+/-10	1225+/-10	1225+/-10	1225+/-10
Unit weight [kg]	120	135	165	180	250	370
Refrigerant	R404A / R507	R404A / R507	R404A / R507	R404A / R507	R404A / R507	R404A / R507
Evaporating temperature [°C]	-10	-10	-10	-10	-10	-10
Cooling power demand [W/mb]	400	400	400	400	400	400
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	14,4	17	22,4	28,8	34	51
Rated power [W]	19	22	27	39	49	66
Electricity consumption [kWh/24h]	0,3	0,3	0,4	0,6	0,7	1

Standard equipment

powered only by external aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of stainless steel

rear storage compartment door - hinged (not applicable to corners)

grey granite worktop (thickness 20 mm)

internal frame and aluminum profiles anodised color silver or gold (IGLOO pattern book)

front glass – telescopic lifting system

night blinds made of plexi glass

LED lamp (color of choice: white, confectionery or meaty “deep pink”)

bumper - different colors available (IGLOO pattern book)

insulated plastic side walls + glass side panels – different colors available (IGLOO pattern book)

automatic defrost

electronic temperature controller with digital display (IGLOO)

Options

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

wooden sides + glass sides - selectable colour (IGLOO colour chart) (applies to DRE and CUSTOM versions)

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color – different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid – resistant stainless steel

exposition stepped overlay made of stainless steel (1 step)

exposition stepped overlay made of acid resistant stainless steel (1 step)

exposition stepped overlay made of stainless steel (2 step)

exposition stepped overlay made of acid resistant stainless steel (2 step)

powder painted evaporator

worktop – granite Balmoral (thickness : 20 mm)

worktop – granite black (thickness : 20 mm)

worktop – stainless steel

additional exposition glass shelf

additional LED light in top lamp profile

automatic defrost

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

analog thermometer

electronic temperature recorder + software

recorder cable

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

