



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a**

Specifications	SANTIAGO 1.1 WG	SANTIAGO 1.4 WG	SANTIAGO 1.7 WG	SANTIAGO 2.1 WG	SANTIAGO 2.5 WG	SANTIAGO 3.75 WG
CODE	SA100WG	SA101WG	SA102WG	SA103WG	SA104WG	SA180WG
Length [mm]	1040	1370	1670	2000	2540	3830
Capacity [dm ³]	143	192	237	286	366	558
Cooling area of shelves [m ²]	0,86	1,16	1,43	1,73	2,21	3,38
Side panel thickness [mm]	40	40	40	40	40	40
Depth [mm]	1190	1190	1190	1190	1190	1190
Height [mm]	1225+/-10	1225+/-10	1225+/-10	1225+/-10	1225+/-10	1225+/-10
Unit weight [kg]	145	165	195	220	295	420
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a
Evaporating temperature [°C]	-10	-10	-10	-10	-10	-10
Cooling power demand [W/mb]	400	400	400	400	400	400
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	14,4	17	22,4	28,8	34	51
Rated power [W]	320	406	411	604	680	1128
Cooling power [W]	520	686	686	710	1050	2057
Electricity consumption [kWh/24h]	4,8	5,7	5,7	9,1	9,5	16,9

Standard equipment

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

internal cooling aggregate

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of stainless steel

rear storage compartment door - hinged (not applicable to corners)

grey granite worktop (thickness 20 mm)
internal frame and aluminum profiles anodised color silver or gold (IGLOO pattern book)
front glass - telescopic lifting system
night blinds made of plexi glass
lampa ze świetłówką LED (barwa do wyboru)
bumper - different colors available (IGLOO pattern book)
insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)
automatic defrost
condenser outlet to container
electronic temperature controller with digital display (IGLOO)
condenser impurity or fan operation failure alarm

Options

device prepared for multiplexing
wooden sides + glass sides - selectable colour (IGLOO colour chart) (applies to DRE and CUSTOM versions)
device without side panels prepared for multiplexing (MOD/A)
housing with base panel from staff side made of stainless steel
front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)
front panel color - different colors available (IGLOO pattern book)
custom front panel color (after consultation with the IGLOO Sales Department)
base panel made of stainless steel
exposition area made of acid resistant stainless steel
storage chamber made of acid - resistant stainless steel
exposition stepped overlay made of stainless steel (1 step)
exposition stepped overlay made of acid resistant stainless steel (1 step)
exposition stepped overlay made of stainless steel (2 step)
exposition stepped overlay made of acid resistant stainless steel (2 step)
powder painted evaporator
worktop - granite Balmoral (thickness : 20 mm)
worktop - granite black (thickness : 20 mm)
worktop - stainless steel
additional exposition glass shelf
set of wheels (castors)
additional LED light in top lamp profile
automatic defrost
the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)
automatic condenser vaporization
analog thermometer
electronic temperature recorder + software
recorder cable
socket with fuse
customer front shelf (aluminum profile anodised color silver or gold)
movable partition (low ,glass on stands , placed in exposition area)
top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

